

## Thermoelectric cooling unit TG 6405305




### Product Features

<b>Brand Name:</b>	SoliTherm Peltier
<b>Order Number:</b>	6405305
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>IP class EN 60529:</b>	IP 66 NEMA 4X
<b>Optional:</b>	Stainless Steel 316 with Chromated heatsinks, P/N: 64053054
<b>Approvals:</b>	CE, RoHS
<b>Accessories:</b>	<a href="#">Condensate Kit</a>
<b>Taric Code:</b>	84158300


## Technical data TG 6405305

<b>Cooling capacity L35L35:</b>	400 W
<b>Temperature range:</b>	-20°C - +65°C
<b>Air volume flow:</b>	Ambient air circuit: 240 m <sup>3</sup> /h Cabinet air circuit: 240 m <sup>3</sup> /h
<b>Mounting:</b>	External (with frame)
<b>Dimension HxWxD:</b>	600 x 430 x 212.5 mm
<b>Weight:</b>	37 kg
<b>Voltage / Frequency:</b>	120 - 230 V ~ 50/60 Hz
<b>Current L35L35:</b>	4.0 A @ 120 V 2.1 A @ 230 V
<b>Max. current:</b>	5.6 A @ 120 V 3 A @ 230 V
<b>Nominal power L35L35:</b>	482 W
<b>Max. power:</b>	660W
<b>Fuse:</b>	10 A @ 120 V 5 A @ 230 V
<b>Connection:</b>	8-Pole Connector

Please click on the graphics to download.  
 More CAD drawings can be found under [Product Download](#).  
 > [Overview product group Cabinet cooling units - Peltier](#)

**Performance Graph:**


click image to enlarge

**Cut out dimensions:**


click image to enlarge